



WARNING!

1.877.FASTOYS

TRINITY RACING DOES NOT TAKE RESPONSIBILITY FOR DAMAGES THAT MAY OCCUR DURING OPERATION OF YOUR VEHICLE UNDER IMPROPER JET SETTINGS. IT IS THE FINAL RESPONSIBILITY OF THE OWNER/RIDER TO ADJUST JETTING TO SPECIFIC RIDING CONDITIONS AND ELEVATION BEFORE RIDING.

PLEASE FOLLOW ALL OF THESE INSTRUCTIONS CAREFULLY.

BANSHEE STAGE IV FILTER INSTRUCTIONS

1. Remove the stock airbox, filter, and filter cage. Clean your airbox thoroughly.
2. Place billet adapter against the airbox and make sure the adapter is secured on the bottom groove of the airbox, then mark holes against the airbox with scribe.
3. Use a 17/64" drill bit and drill the holes you marked on the airbox. Clean all loose materials out of the airbox.
4. Install the o-ring into the adapter and use a light film of grease to hold the o-ring in place. Install the securing bolts and use Lock-tite on bolts. Tighten securely.
5. Install the Ourterwear over the filter. Install the filter onto the flange. Make sure the filter is snug and tighten the filter clamp. Be sure to place the clamp screw to the side of the flange to ensure the lid will fit.
6. Reassemble everything and then check your jetting to make sure it is appropriate for your riding conditions.

That's it, enjoy your new powerflow air filter system!

THANK YOU FOR YOUR BUSINESS. HAVE A FUN AND SAFE RIDE!