



WARNING!

1.877.FASTOYS

TRINITY RACING DOES NOT TAKE RESPONSIBILITY FOR DAMAGES THAT MAY OCCUR DURING OPERATION OF YOUR VEHICLE UNDER IMPROPER JET SETTINGS. IT IS THE FINAL RESPONSIBILITY OF THE OWNER/RIDER TO ADJUST JETTING TO SPECIFIC RIDING CONDITIONS AND ELEVATION BEFORE RIDING.

Due to the variable riding conditions and limitations of the powdercoating process, Trinity Racing cannot guaranty the optional powdercoated colors life expectancy on our billet accessories.

PLEASE FOLLOW ALL OF THESE INSTRUCTIONS CAREFULLY.

BLASTER EXHAUST INSTRUCTIONS

- 1 Head Pipe (Mild Steel)
- 1 Exhaust Flange (Mild Steel)
- 1 Stinger (Mild Steel) w/ Muffler (Aluminum)
- 1 Small Spring
- 1 Instruction Sheet w/ Jetting Specs

INSTALLATION INSTRUCTIONS

Save your stock parts. Some will be used for installation of new pipe (ie; front frame mounts, springs, etc).

1. Remove your stock exhaust system.
2. Slide the header pipe into the exhaust flange and hold together with the small spring (you can use high temperature silicone to seal the fange to the engine. If desired, you can also had some to the header pipe where it slides into the flange).
3. Place the header pipe into place and use the stock header bolts and stock frame mount to hold it in place. Do not completely tighten the bolts yet (should point to the right side of the quad).
4. Slide the muffler into place. Use the stock bolts and mo7unting tabs to hold the muffler in place at the stock locations.
5. Go over the complete system and tighten all the nuts and bolts before starting the bike.
6. Re-jetting is REQUIRED when adding performance parts to the bike (ie. pipe, filter kit, motor mods, etc...).
7. Do a spark plug test to see if your bike is running lean or fat and adjust the jetting accordingly.

JETTING SPECIFICATIONS

Jetting specs provided are for a stock motor with a Trinity Racing Stage IV Exhaust System at sea level. Other performance mods to your bike usually require changes in jetting. Final jetting is the customer's responsibility.

MAIN JET	PILOT JET	CLIP POSITION	NEEDLE	FUEL/AIR SCREW	AIRBOX
270	32.5	#4	Stock		Stock

THANK YOU FOR YOUR BUSINESS. HAVE A FUN AND SAFE RIDE!