



OVERSIZED ROTOR KIT

YAMAHA XYZ1000R INSTALLATION INSTRUCTIONS

#F2-OS17

PARTS LIST

1. 1 x Left oversized blade rotor
2. 1 x Right oversized blade rotor
3. 2 x Oversized billet caliper brackets



CALIPER BRACKET INSTALLATION

Please Note: Be sure to match up the correct oversized caliper bracket with the matching OEM bracket before installing this kit.

1. Beginning on side, lift the Rear of the vehicle off of the ground until the tire is no longer touching the floor (We highly recommend the use of a sturdy jack stand to hold the vehicle in place while the kit is installed. Remove the wheel and place to the side.
2. Remove the 2 caliper bracket bolts that attached the caliper to the spindle and remove the caliper from the spindle.
3. Remove the rotor guard if installed from the caliper bracket. Next remove the caliper and slide out the OEM caliper bracket.
4. Install the new oversized caliper bracket. Before installing the new caliper bracket, lube the new oversized caliper bracket pins with high temp brake grease.
5. Install the brake pads and place the completed caliper to the side. We recommend installing brand new brake pads with every brand new rotor.

ROTOR INSTALLATION

1. Remove the spindle cotter pin and spindle nut and slide the brake hub off of the spindle.
2. Remove the 4 rotor mounting bolts and install the new oversized Blade rotor. All rotor bolts should be tightened to OEM torque specifications. (Fig. 1)
3. Re-install the brake hub back onto the spindle. We recommend adding fresh wheel bearing grease to the spindle and inner brake hub splines.
4. Re-install the spindle nut followed with a new cotter pin. The spindle nut should be tightened to OEM torque specifications.

- If you have any questions, please contact Trinity Racing Tech Support.



5221 Oceanus Drive,
Huntington Beach, CA 92649

714-988-0339
trinityracing.com